

AT-GP-120-S


<b>Standards</b>	
Pole Design	AS 4676 / AS 1170.2 Sectn4 / NZS 4203
Material	EN 12767 Class 0 / BS 4360 / BS EN 10025
Welding (Electric Arc Welding)	AS 1554
Galvanising	AS / NZS 4680
<b>Testing Procedures</b>	
	Dimensional Verification
	Galvanising Thickness
	Material Thickness
<b>Quality Control Procedures</b>	
	The Supplier/Manufacturer and Galvanizer of the column shall be ISO 9001 : 2000 accredited
<b>Finishing Types</b>	
	Oven Baked Powder Coated
	High Performance Polyester UV Resistance. (formulated for galvanized surface)
	Hot Dip Galvanized
	2 Part Epoxy Coat (10 Years)
<b>Foundation Design</b>	
	Foundation Design by others
	PS1 Designs by Request

**Other Information**

Gear Door - 300mm x 150mm  
 Cable Entry - 150mm x 75mm

Protective Epoxy Paint (Sigmashield 880) to ATCoP Standards. From 200mm above ground level to section bottom.

This drawing and the information contained herein, is the sole property of Steelgal NZ Limited and may not be used without consent from Steelgal NZ Limited.

Rev	Details	By	Chd	Date	Drawn: <b>DDC</b> Date: <b>23.05.2018</b> Scale: <b>NTS</b> Checked: Approved: Date:	Title: <b>12.0m ATCoP Octagonal Streetlight Pole with Planted Base</b> Drawing Number: <b>AT-GP-120-S</b> Customer:	 <b>STEELGAL NZ LIMITED</b>	Steelgal NZ Limited 8 Trugood Drive East Tamaki Auckland P: 0800 736600 F: (+649) 2724665 E: sales@steelgal.co.nz W: www.steelgal.co.nz
-----	---------	----	-----	------	---	--	---	---