

# AT-GP-080-S

## Standards

Pole Design AS 4676 / AS 1170.2 Sect'n4 / NZS 4203  
 Material EN 12767 Class 0 / BS 4360 / BS EN 10025  
 Welding (Electric Arc Welding) AS 1554  
 Galvanising AS / NZS 4680

## Testing Procedures

Dimensional Verification  
 Galvanising Thickness  
 Material Thickness

## Quality Control Procedures

The Supplier/Manufacturer and Galvanizer of the column shall be ISO 9001 : 2000 accredited

## Finishing Types

Oven Baked Powder Coated  
 High Performance Polyester UV Resistance. (formulated for galvanized surface)  
 Hot Dip Galvanized  
 2 Part Epoxy Coat (10 Years)

## Foundation Design

Foundation Design by others  
 PS1 Designs by Request


## Other Information

Gear Door - 300mm x 150mm

Cable Entry - 150mm x 75mm

Protective Epoxy Paint (Sigmashield 880) to ATCoP Standards. From 200mm above ground level to section bottom.

This drawing and the information contained herein, is the sole property of Steelgal NZ Limited and may not be used without consent from Steelgal NZ Limited.

Rev	Details	By	Chd	Date	Drawn: <b>DDC</b>	Title: <b>8.0m ATCoP Octagonal Streetlight Pole with Planted Base</b>		Steelgal NZ Limited 8 Trugood Drive East Tamaki Auckland P: 0800 736600 P: (+649) 2724665 F: (+649) 2724669 E: sales@steelgal.co.nz W: www.steelgal.co.nz
					Date: <b>23.05.2018</b>			
					Scale: <b>NTS</b>			
					Checked:			
					Approved:			
Date:	Drawing Number: <b>AT-GP-080-S</b>	Customer:						