

Technical Specification

Design Conditions

1. Design Conditions	
1.1 Basic wind speed	: 45 m/s
1.2 Max Luminaire sail area	: 0.10 m ²
1.3 Max Luminaire weight	: 8 kg
1.4 Terrain Category	: TC 2
1.5 Total number of sections	: 1

Standards

Pole design	AS 4676 / AS 1170.2 Sec/n4 / NZS 4203
Material	EN 12767 Class 0 / BS 4360 / BS EN 10025
Welding (Electric Arc Welding)	AS 1554
Galvanising	AS / NZ 4680

Testing Procedures

Dimensional Verification
Galvanising Thickness
Material Thickness

Quality Control Procedures


The Supplier/Manufacturer and Galvanizer of the column shall be ISO 9001: 2000 accredited

Finishing Types

Oven Baked Powder Coated
High Performance Polyester UV Resistance.
(formulated for galvanized surface)
Hot Dip Galvanized
2 Part Epoxy Coat (10 Years)

SLS Outreach Options

Curved Outreaches



This drawing and the information contained herein, is the sole property of Steelgal NZ Limited and may not be used without consent from Steelgal NZ Limited.

Drawn:	RY	Date:	27.09.2013	Title:	6.0m Octagonal Streetlight Column with Planted Base - 1M Curved Outreach
Scale:	NTS	Checked:		Drawing Number:	AT-SLS-060-P-1M COR
Approved:		Customer:			
Rev	Details	By	Chd	Date	

Steelgal NZ Ltd
8 Trugood Drive
East Tamaki Auckland
P: (+649) 2724665
F: (+649) 2724669
E: sales@steelgal.co.nz
W: www.steelgal.co.nz