


This drawing and the information contained herein, is the sole property of Steelgal NZ Limited and may not be used without consent from Steelgal NZ Limited.



AT-GP-140-D

Standards

Pole Design AS 4676 / AS 1170.2 Sect'n4 / NZS 4203
 Material EN 12767 Class 0 / BS 4360 / BS EN 10025
 Welding (Electric Arc Welding) AS 1554
 Galvanising AS / NZS 4680

Testing Procedures

Dimensional Verification
 Galvanising Thickness
 Material Thickness

Quality Control Procedures

The Supplier/Manufacturer and Galvanizer of the column shall be ISO 9001 : 2000 accredited

Finishing Types

Oven Baked Powder Coated
 High Performance Polyester UV Resistance. (formulated for galvanized surface)
 Hot Dip Galvanized
 2 Part Epoxy Coat (10 Years)

Foundation Design

Foundation Design by others
 PS1 Designs by Request

Other Information

Gear Door - 300mm x 150mm

Cable Entry - 150mm x 75mm

Protective Epoxy Paint (Sigmashield 880) to ATCoP Standards. From 200mm above ground level to section bottom.

Drawn:	DDC	Title:	12.0m ATCoP Octagonal Streetlight Pole with Planted Base				
Date:	23.05.2018						
Scale:	NTS						
Checked:							
Approved:		Drawing Number:	AT-GP-120-S				
Rev	Details	By	Chd	Date	Date:	Customer:	



Steelgal NZ Limited
 8 Trugood Drive
 East Tamaki Auckland
 P: 0800 736600
 F: (+649) 2724665
 E: sales@steelgal.co.nz
 W: www.steelgal.co.nz